

Technical data sheet 102G6

Specification Swivel chair, FLEXTECH, low

Dimensions in mm	Backrest:	H:	430
		Seat:	H: 400-525
		W:	500
		D:	470
	Total:	H:	1125
		W (no ArmR):	510
W (ArmR):		710	
D:		630	
Packaging data	Weight:	kg	18,5
	Volume:	m³	0,2



Basic equipment

Benefit

Backrest	Back low, upholstered 30 mm foam + 10 mm cotton. Rear side of the backrest plastic cover. Height adjustable backrest comfortable and easy to handle according to the individual requirements of each person, also when sitting. With an adjustment area of 7 positions (70 mm). Backrest lockable in 4 positions.	The back mainly has to be supported in the area of the 4th and 5th lumbar vertebra. Can be adjusted to short and tall users. EN 1335 only demands locking in the foremost seating position. Our mechanism allows to sit comfortably in the middle and rear seating positions too. The backrest cannot accidentally spring forwards even after unlocking.
Upholstery	Seat and back upholstered. Breath actively moulding foam, CFC - CHC - free (pure foam). Seat 50 mm foam.	Upholstery is unglued, ensuring optimal air movement, breathable.
Mechanism	Synchronous mechanism, lockable, with FLEXTECH Inside. Opening angle between seat and back up to 105° with additional side tilt of 5°.	Synchronous mechanisms of Interstuhl are designed in a way that they help to support optimally the body in every seating position and at the same time they relieve the change between the different seating positions. This is also aided by FLEXTECH and enables dynamic 3D sitting.
Seat height adjustment	Seat height adjustment infinitely variable from 400 - 525 mm. Self- supporting safety gas spring.	People measuring with a height between 151 and 192 cm (Acc. to DIN EN 1335) can individually adjust the seat height in the most ergonomic way.
Seat inclination	Integrated seat tilt feature thanks to FLEXTECH Inside, 5° to the side, 5° to the front.	The inclination means that the pelvis is at a steeper angle and the spine is straightened, thus preventing rounding of the back. Enables dynamic 3D sitting.
Weight adjustment	From 45 - 125 kg, adjustable within 7 steps.	Individual adjustment of the backrest and back pressure to the weight and height of the user.
Base	Polyamide base black.	Very high stability, longevity.
Materials	All materials are pure and recyclable.	Environmentally friendly.
Standards	EN 1335 for office swivel chairs and office swivel armchairs. GS-symbol for tested safety, tested for harmful substances and ergonomics.	High level of safety and comfort.
Certification	Quality management system DIN EN ISO 9001:2015, Regulation (EC) no. 1221/2009 (EMAS), Environmental Management System DIN EN ISO 14001:2015, Health and Safety Management System DIN ISO 45001:2018, Energy management system DIN EN ISO 50001:2018, EcoVadis Gold, Commitment to sustainability. Quality Office, Blue Angel, Bifma e3 level Platin.	High-quality product.

Technical data sheet 102G6

Specification Swivel chair, FLEXTECH, low

Dimensions in mm	Backrest:	H:	430	
		Seat:	H:	400-525
			W:	500
	Total:	D:	470	
		H:	1125	
		W (no ArmR):	510	
		W (ArmR):	710	
Packaging data	Weight:	kg	18,5	
		D:	630	
	Volume:	m³	0,2	



Warranty 10-year warranty according to our current warranty conditions.

Quality guaranteed to last for entire product life.

Technical data sheet 102G6

Specification Swivel chair, FLEXTECH, low

Dimensions in mm	Backrest:	H:	430
		Seat:	H: 400-525
		W:	500
		D:	470
	Total:	H:	1125
		W (no ArmR):	510
W (ArmR):		710	
D:		630	
Packaging data	Weight:	kg	18,5
	Volume:	m³	0,2



Options

Benefit

Castors Ø 65 mm	Hard castors, load- dependent braked, for soft floors (according to DIN EN 12529).	The unoccupied chair does not roll away unintentionally.
Castors Ø 65 mm	Soft castors, load- dependent braked, for hard floors (acc. to DIN EN 12529) or glides.	The unoccupied chair does not roll away unintentionally.
Base	Aluminium base powder coated black, brillantsilver or aluminium polished.	Very high stability, longevity.
Seat height adjustment	Seat height adjustment infinitely variable: Self-supporting safety gas spring low: 395 - 445 mm; Self-supporting safety gas spring high: 465 - 600 mm.	Even for people taller than 192 cm and smaller than 151 cm is offered the correct ergonomic seating posture.
Mechanical sprung column	Standard chair column optionally available with mechanical sprung column in the lowest seating position.	Damping of an excessive vertical impact, so that the spine will be preserved.
Seat depth adjustment	Sliding seat for an individual adjustment of the seat depth, area of adjustment 50 mm.	The seat depth can be individually adjusted to ensure an optimal support surface of the thighs.
Lumbar support	Depth- adjustable lumbar support.	Through a mechanical rotation the lumbar support which is integrated in the back upholstery will be adjusted horizontally and will be adapted to the corporal conditions of the user. In that way an individual support in the lumbar area is possible.
Armrests	2D T-armrests, height and width adjustable, soft surface. 4D T-armrest, height, width and depth adjustable, rotatable, soft surface.	The armrests relieve the neck and shoulder muscles.
Material	Various fabrics in a variety of colours are available.	A great variety of design possibilities.
Two- colour design	Certain fabric qualities allow within the same fabric collection two different upholstery colours for seat and back covers.	Optical design.