# interstuhl

### Technical data sheet 152G6

Specification Swivel chair, FLEXTECH, medium

Dimensions in mm	Backrest:	H:	530
	Seat:	H:	400-525
		W:	500
		D:	470
	Total:	H:	1225
		W (no ArmR):	510
		W (ArmR):	710
		D:	630
Packaging data	Weight:	kg	19,5
	Volume:	m³	0,2



Benefit

#### Basic equipment

Backrest	Back medium high, upholstered 30 mm foam + 10 mm cotton. Rear side of the backrest plastic cover. Height adjustable backrest comfortable and easy to handle according to the individual requirements of each person, also when sitting. With an adjustment area of 7 positions (70 mm). Backrest lockable in 4 positions.	The back mainly has to be supported in the area of the 4th and 5th lumbar vertebra. Can be adjusted to short and tall users. EN 1335 only demands locking in the foremost seating position. Our mechanism allows to sit comfortably in the middle and rear seating positions too. The backrest cannot accidentally spring forwards even after unlocking.
Upholstery	Seat and back upholstered. Breath actively moulding foam, CFC - CHC - free (pure foam). Seat 50 mm foam.	Upholstery is unglued, ensuring optimal air movement, breathable.
Mechanism	Synchronous mechanism, lockable, with FLEXTECH Inside. Opening angle between seat and back up to 105° with additional side tilt of 5°.	Synchronous mechanisms of Interstuhl are designed in a way that they help to support optimally the body in every seating position and at the same time they relieve the change between the different seating positions. This is also aided by FLEXTECH and enables dynamic 3D sitting.
Seat height adjustment	Seat height adjustment infinitely variable from 400 - 525 mm. Self- supporting safety gas spring.	People measuring with a height between 151 and 192 cm (Acc. to DIN EN 1335) can individually adjust the seat height in the most ergonomic way.
Seat inclination	Integrated seat tilt feature thanks to FLEXTECH Inside, 5° to the side, 5° to the front.	The inclination means that the pelvis is at a steeper angle and the spine is straightened, thus preventing rounding of the back. Enables dynamic 3D sitting.
Weight adjustment	From 45 - 125 kg, adjustable within 7 steps.	Individual adjustment of the backrest and back pressure to the weight and height of the user.
Castors Ø 65 mm	Hard castors, load- dependent braked, for soft floors (according to DIN EN 12529).	The unoccupied chair does not roll away unintentionally.
Base	Polyamide base black.	Very high stability, longevity.
Materials	All materials are pure and recyclable.	Environmentally friendly.
Standards	EN 1335 for office swivel chairs and office swivel armchairs. GS-symbol for tested safety, tested for harmful substances and ergonomics.	High level of safety and comfort.

# interstuhl

### Technical data sheet 152G6

Specification Swivel chair, FLEXTECH, medium

Dimensions in mm	Backrest:	H:	530	
	Seat:	H:	400-525	
	0000	W:	500	
		D:	470	
	Total:			T T
		H:	1225	
		W (no ArmR):	510	
		W (ArmR):	710	
		D:	630	
Packaging data	Weight:	kg	19,5	
	Volume:	m³	0,2	
Certification			ment system DIN EN ISO	High-quality product.
			ulation (EC) no. 1221/2009	
			mental Management System 01:2015, Health and Safety	
			stem DIN ISO 45001:2018,	
			ment system DIN EN ISO	
			oVadis Gold, Commitment to	
		sustainability. Qi e3 level Platin.	uality Office, Blue Angel, Bifma	
Morronty			· · · · · · · · · · · · · · · · · · ·	Quality succession to lost for antire preduct life
Warranty		10-year warranty warranty condition	y according to our current	Quality guaranteed to last for entire product life.

# interstuhl

### Technical data sheet 152G6

Options

Specification Swivel chair, FLEXTECH, medium

Dimensions in mm	Backrest:	H:	530
	Seat:	H:	400-525
		W:	500
		D:	470
	Total:	H:	1225
		W (no ArmR):	510
		W (ArmR):	710
		D:	630
Packaging data	Weight:	kg	19,5
	Volume:	m³	0,2



Benefit

Castors Ø 65 mm	Soft castors, load- dependent braked, for hard floors (acc. to DIN EN 12529) or glides.	The unoccupied chair does not roll away unintentionally.
Base	Aluminium base powder coated black, brillantsilver or aluminium polished.	Very high stability, longevity.
Seat height adjustment	Seat height adjustment infinitely variable: Self-supporting safety gas spring low: 395 - 445 mm; Self-supporting safety gas spring high: 465 - 600 mm.	Even for people taller than 192 cm and smaller than 151 cm is offered the correct ergonomic seating posture.
Nechanical sprung column	Standard chair column optionally available with mechanical sprung column in the lowest seating position.	Damping of an excessive vertical impact, so that the spine will be preserved.
Seat depth adjustment	Sliding seat for an individual adjustment of the seat depth, area of adjustment 50 mm.	The seat depth can be individually adjusted to ensure an optimal support surface of the thighs.
Lumbar support	Depth- adjustable lumbar support.	Through a mechanical rotation the lumbar support which is integrated in the back upholstery will be adjusted horizontally and will be adapted to the corporal conditions of the user. In that way an individual support in the lumbar area is possible.
Armrests	2D T-armrests, height and width adjustable, soft surface. 4D T-armrest, height, width and depth adjustable, rotatable, soft surface.	The armrests relieve the neck and shoulder muscles.
Material	Various fabrics in a variety of colours are available.	A great variety of design possibilities.
Two- colour design	Certain fabric qualities allow within the same fabric collection two different upholstery colours for seat and back covers.	Optical design.