

Technical data sheet 1S066

Specification Swivel chair low, Chillback, FLEXTECH

| Dimensions in mm | Backrest: | H: | 650 |
|------------------|-----------|--------------|---------|
| | Seat: | H: | 400-525 |
| | | W: | 500 |
| | | D: | 470 |
| | Total: | H: | 1240 |
| | | W (no ArmR): | 510 |
| | | W (ArmR): | 710 |
| | | D: | 590 |
| Packaging data | Weight: | kg | 14,50 |
| | Volume: | m³ | 0,64 |
| | | | |



| Basic equipment | | Benefit |
|------------------------|---|---|
| Plastic parts | Colour maintained throughout, black. | Colourfast and resistant to deep scratches and abrasions. |
| Backrest | Back low, upholstered mesh backrest (Chillback). Height adjustable backrest comfortable and easy to handle according to the individual requirements of each person, also when sitting. With an adjustment area of 5 positions (each 12 mm). Backrest locking 4 positions. | |
| Upholstery | Seat upholstery: 55 mm foam, upholstery is unglued, ensuring optimal air movement, breathable. | Great seating comfort. |
| Mechanism | Synchronous mechanism lockable thanks to FLEXTECH Inside. Large opening angle of up to max. 118° between seat and backrest with additional side tilt of 4°. | Synchronous mechanisms of Interstuhl are designed in a way that they help to support optimally the body in every seating position and at the same time they relieve the chang between the different seating positions. This is also aided by FLEXTECH and enables dynamic 3D sitting. |
| Seat height adjustment | Seat height adjustment infinitely variable from 405 - 530 mm. Self-supporting safety gas spring. | Even people outside the DIN range (i.e. taller than 192cm and smaller than 151cm) will sit in the most ergonomic way. |
| Weight Adjustment | From 45 - 120 kg, adjustable within 7 steps. | Individual adjustment of the backrest and the back pressure to the weight and height of the user. |
| Seat inclination | Integrated seat tilt feature thanks to FLEXTECH Inside. | The inclination means that the pelvis is at a steeper angle and the spine is straightened, thus preventing rounding of the back. |
| Castors Ø 65 mm | Hard double castors, black, load dependent braked, for soft floors. (Acc. to DIN EN 12529). | The chair does not roll away in an off-loaded situation, minimum risk of accident. |
| Base | Colour maintained throughout polyamide base, black. | Colourfast and resistant to deep scratches and abrasions. |
| Materials | All materials are segregated and recyclable. | Environmentally friendly. |
| Standards | EN 1335 for office swivel chairs and office swivel armchairs. GS-Symobl for tested safety, tested for contaminants, Ergonomics approved. | High quality product and great comfort. |

AlMis1



Exchange of parts free of charge within the guaranteed

period.

Technical data sheet 1S066

Warranty and return

Specification Swivel chair low, Chillback, FLEXTECH

| Dimensions in mm | Backrest: | H: | 650 | |
|---------------------|-----------|------------------|--|---|
| | Seat: | H: | 400-525 | |
| | | W: | 500 | |
| | | D: | 470 | T |
| | Total: | H: | 1240 | |
| | | W (no ArmR): | 510 | |
| | | W (ArmR): | 710 | |
| | | D: | 590 | T |
| Packaging data | Weight: | kg | 14,50 | |
| | Volume: | m³ | 0,64 | A ' |
| | | | | |
| Certification | | , , | ment system DIN EN ISO | High quality product. |
| | | | (EG) No. 1221/2009 (EMAS), nanagement system DIN EN | |
| | | | O, OHSAS, EcoVadis gold, | |
| | | | sustainability. Quality Office, | |
| | | Blue Angel. Bifm | na e3 level Platin. | |
| Marranty and raturn | | 40 | to Camaniata natura and | Freehouse of control of the control of the control of |

10 years warranty. Complete return and

recycling guarantee.

Disassembly instructions are available upon request for any interstuhl product



Technical data sheet 1S066

Specification Swivel chair low, Chillback, FLEXTECH

| Dimensions in mm | Backrest: | H: | 650 |
|------------------|-----------|--------------|---------|
| | Seat: | H: | 400-525 |
| | | W: | 500 |
| | | D: | 470 |
| | Total: | H: | 1240 |
| | | п. | 1240 |
| | | W (no ArmR): | 510 |
| | | W (ArmR): | 710 |
| | | D: | 590 |
| Packaging data | Weight: | kg | 14,50 |
| | Volume: | m³ | 0,64 |



| Options | | Benefit |
|-----------------------|--|---|
| Castors/Glides | Soft double castors, load dependent braked, for hard floors or glides hard/soft. (Acc. to DIN EN 12529). | The chair does not roll away in an off-loaded position, minimum risk of accident. |
| Base | Polished aluminium base. | Very high stability, long service life. High-quality look. |
| Seat depth adjustment | Individual adjustment of the seat depth, 60 mm adjustment. | |
| Lumbar support | Height adjustable (14 mm). | Through a mechanical rotation the lumbar support which is integrated in the back upholstery will be adjusted horizontally and will be adapted to the corporal conditions of the user. In that way an individual support in the lumbar area is possible. |
| Armrests | 2D T-armrests, height and width adjustable, soft surface. 4D T-armrest, height, width and depth adjustable, rotatable, soft surface. | The armrests relieve the neck and shoulder muscles. |
| Meterial (fabric) | Various fabric and leather options available. | Individual design. |
| Accessories | Coat hanger polyamide, black. | |

Disassembly instructions are available upon request for any interstuhl product