

Technical data sheet 1S24

Specification Swivel armchair high, mesh, Synchron

Dimensions in mm	Backrest:	H:	720
	Seat:	H:	400-525
		W:	500
		D:	470
	Total:	H:	1310
		W (no ArmR):	510
		W (ArmR):	710
		D:	590
Packaging data	Weight:	kg	14,30
	Volume:	m³	0,68



Basic equipment		Benefit
Plastic parts	Colour maintained throughout, black.	Colourfast and resistant to deep scratches and abrasions.
Backrest	Back high, black mesh backrest. Height adjustable backrest comfortable and easy to handle according to the individual requirements of each person, also when sitting. With an adjustment area of 5 positions (each 12 mm). Backrest locking 4 positions.	
Upholstery	Seat upholstery: 55 mm foam, upholstery is unglued, ensuring optimal air movement, breathable.	Great seating comfort.
Mechanism	Synchronous mechanism. Large opening angle between seat and back until max 118°.	Synchronous mechanisms of Interstuhl are designed in a way that they help to support optimally the body in every seating position and at the same time they relieve the chang between the different seating positions.
Seat height adjustment	Seat height adjustment infinitely variable from 405 - 530 mm. Self-supporting safety gas spring.	Even people outside the DIN range (i.e. taller than 192 cm and smaller than 151cm) will sit in the most ergonomic way.
Weight Adjustment	From 45 - 120 kg, adjustable within 7 steps.	Individual adjustment of the backrest and the back pressure to the weight and height of the user.
Castors Ø 65 mm	Hard double castors, black, load dependent braked, for soft floors. (Acc. to DIN EN 12529).	The chair does not roll away in an off-loaded situation, minimum risk of accident.
Base	Colour maintained throughout polyamide base, black.	Colourfast and resistant to deep scratches and abrasions.
Materials	All materials are segregated and recyclable.	Environmentally friendly.
Standards	EN 1335 for office swivel chairs and office swivel armchairs. GS-Symobl for tested safety, tested for contaminants, Ergonomics approved.	High quality product and great comfort.



Technical data sheet 1S24

Specification Swivel armchair high, mesh, Synchron

Dimensions in mm	Backrest:	H:	720
	Seat:	H:	400-525
		W:	500
		D:	470
	Total:	H:	1310
		W (no ArmR):	510
		W (ArmR):	710
		D:	590
Packaging data	Weight:	kg	14,30
	Volume:	m³	0,68



Certification Quality Management System DIN EN ISO

9001:2015, Regulation (EC) no. 1221/2009 (EMAS), Environmental Management System DIN EN ISO 14001:2015, Occupational Health and Safety Management System DIN ISO 45001:2018, Energy Management System DIN EN ISO 50001:2018, EcoVadis Gold,

Commitment to sustainability. Quality Office, Blue Angel, Bifma e3 level Platin.

10-year warranty according to our current warranty conditions.

Quality guaranteed to last for entire product life.

Warranty

AlMis1



Technical data sheet 1S24

Options

Specification Swivel armchair high, mesh, Synchron

Dimensions in mm	Backrest:	H:	720
	Seat:	H:	400-525
		W:	500
		D:	470
	Total:	H:	1310
		W (no ArmR):	510
		W (ArmR):	710
		D:	590
Packaging data	Weight:	kg	14,30
	Volume:	m³	0,68



Benefit

Soft double castors, load dependent braked, for hard floors or glides hard/soft. (Acc. to DIN EN 12529).	The chair does not roll away in an off-loaded position, minimum risk of accident.
Polished aluminium base.	Very high stability, long service life. High-quality look.
Tilting the seat, 2 positions (0° and +4,9°).	The inclination prevents the pelvis from tilting to the reat, ensures the right position of the spinal column.
Individual adjustment of the seat depth, 60 mm adjustment.	
Height adjustable (15 mm).	Through a mechanical rotation the lumbar support which is integrated in the back upholstery will be adjusted horizontally and will be adapted to the corporal conditions of the user. In that way an individual support in the lumbar area is possible.
2D T-armrests, height and width adjustable, soft surface. 4D T-armrest, height, width and depth adjustable, rotatable, soft surface.	The armrests relieve the neck and shoulder muscles.
Various fabric and leather options available.	Individual design.
Coat hanger polyamide, black.	
	hard floors or glides hard/soft. (Acc. to DIN EN 12529). Polished aluminium base. Tilting the seat, 2 positions (0° and +4,9°). Individual adjustment of the seat depth, 60 mm adjustment. Height adjustable (15 mm).