

Technical data sheet 5S10

Specification Cantilever frame

Dimensions in mm	Backrest:	H:	470
	Seat:	H:	436
		W:	450
		D:	470
	Total:	H:	905
		W (no ArmR):	500
		D:	550
Packaging data	Weight:	kg	8,95
	Volume:	m³	0,40



Basic equipment		Benefit
Backrest	Seat and back upholstered, breath actively form foam, CFC - CHC - free (segregated foam). Seat 35 mm and back 25 mm.	Paddings are unglued, ensuring optimal air movement, breathable. Good sitting comfort.
Frame	Cantilever frame, powder coated black.	Very high stability, longevity. Coating against scratches, etc.
Seat carrier	Moulded wood, serves at the same time as upholstery carrier.	
Plastic parts	Always black, dyed. Thus "colourfast" also with deep scratches and scars.	Very hard wearing.
Materials	All materials are segregated and recyclable.	Environmentally friendly.
Standards	DIN 16139 four leg and cantilever. GS-Symobl for tested safety, tested for contaminants.	High safety.
Certification	Quality Management System DIN EN ISO 9001:2015, Regulation (EC) no. 1221/2009 (EMAS), Environmental Management System DIN EN ISO 14001:2015, Occupational Health and Safety Management System DIN ISO 45001:2018, Energy Management System DIN EN ISO 50001:2018, EcoVadis Gold, Commitment to sustainability. Quality Office, Blue Angel, Bifma e3 level Platin.	High-quality product.
Warranty	10-year warranty according to our current warranty conditions.	Quality guaranteed to last for entire product life.

AlMis1



Technical data sheet 5S10

Specification Cantilever frame

Dimensions in mm	Backrest:	H:	470
	Seat:	H:	436
		W:	450
		D:	470
	Total:	H:	905
		W (no ArmR):	500
		D:	550
Packaging data	Weight:	kg	8,95
	Volume:	m³	0,40



Options		Benefit
Upholstery materials	Various fabric and leather options available.	Individual design.
Frame	Four leg frame made of tubular steel, chromed.	Very high stability, longevity. High-quality look.
Glides	Felt glides for hard floors.	Optimal positioning of the chair. Saves the floor.