interstuhl

Technical data sheet EV267

Specification Swivel armchair high, mesh, FLEXTECH, Comf.seat

| Dimensions in mm | Backrest: | H: | 730 |
|------------------|-----------|--------------|---------|
| | Seat: | H: | 415-540 |
| | | W: | 520 |
| | | D: | 450 |
| | Total: | H: | 1225 |
| | | W (no ArmR): | 520 |
| | | W (ArmR): | 685 |
| | | D: | 595 |
| Packaging data | Weight: | kg | 15,9 |
| | Volume: | m³ | 0,65 |
| | | | |



| Basic equipment | | Benefit |
|------------------------|---|--|
| Plastic parts | Colour maintained throughout, black or white. | Always look good even with intensive use. |
| Backrest | Backrest high, mesh covered, black. | |
| Upholstery | Seat upholstery: 70 mm foam. Comfort seat. | Upholstery is unglued, ensuring optimal air movement, breathable. Great seating comfort. |
| Mechanism | Synchronous mechanism, lockable, with FLEXTECH Inside. Large opening angle of up to max. 106° with additional side tilt of 5°. Backrest lockable in 4 positions. | Synchronous mechanisms of Interstuhl are designed in a way that they help to support optimally the body in every seating position and at the same time they relieve the change between the different seating positions. This is also aided by FLEXTECH and enables dynamic 3D sitting. |
| Seat height adjustment | Seat height adjustment infinitely variable from 415 - 540 mm. Self-supporting safety gas spring. | People measuring with a height between 151 and 192 cm (Acc. to DIN EN 1335) can individually adjust the seat height in the most ergonomic way. |
| Weight Adjustment | From 45 - 120 kg, multilevel. | Individual adjustment of the backrest and the back pressure to the weight and height of the user. |
| Seat inclination | Integrated seat tilt feature thanks to FLEXTECH Inside, 5° to the side, 5° to the front. | The inclination means that the pelvis is at a steeper angle and the spine is straightened, thus preventing rounding of the back. FLEXTECH expands the range of movement in all directions and therefore guarantees healthier, dynamic sitting. |
| Castors Ø 65 mm | Hard double castors, black, load dependent braked, for soft floors. (Acc. to DIN EN 12529). | The chair does not roll away in an off-loaded position. |
| Base | Polyamide base, colour maintained throughout, black or white. | Always look good even with intensive use. |
| Materials | All materials are pure and recyclable. | Environmentally friendly. |
| Standards | EN 1335 for office swivel chairs and office swivel armchairs. GS-Symbol for tested safety, tested for contaminants, Ergonomics approved. BIFMA. | High level of safety and great comfort. |

Technical data sheet EV267

Certification

Warranty

Specification Swivel armchair high, mesh, FLEXTECH, Comf.seat

| Dimensions in mm | Backrest: | H: | 730 |
|------------------|-----------|--------------|---------|
| | Seat: | H: | 415-540 |
| | | W: | 520 |
| | | D: | 450 |
| | Total: | | |
| | | H: | 1225 |
| | | W (no ArmR): | 520 |
| | | W (ArmR): | 685 |
| | | D: | 595 |
| Packaging data | Weight: | ka | 15,9 |
| Fackaging uata | weight. | kg | 10,0 |
| | Volume: | m³ | 0,65 |
| | | | |

Quality management system DIN EN ISO 9001:2015, Regulation (EC) no. 1221/2009 (EMAS), Environmental Management System

DIN EN ISO 14001:2015, Occupational Health and Safety Management System DIN EN ISO 45001:2018, Energy management system DIN

EN ISO 50001:2018, EcoVadis Gold,

warranty conditions.



High-quality product.

Commitment to sustainability, Quality Office, Blue Angel, Bifma e3 level Platin. 10 year warranty according to our current Quality guaranteed to last for entire product life.

interstuhl

interstuhl

Technical data sheet EV267

Specification Swivel armchair high, mesh, FLEXTECH, Comf.seat

| Dimensions in mm | Backrest: | H: | 730 |
|------------------|-----------|--------------|---------|
| | Seat: | H: | 415-540 |
| | | W: | 520 |
| | | D: | 450 |
| | Total: | | |
| | | H: | 1225 |
| | | W (no ArmR): | 520 |
| | | W (ArmR): | 685 |
| | | D: | 595 |
| Packaging data | Weight: | kg | 15,9 |
| | Volume: | m³ | 0,65 |
| | | | |



Benefit

Options

| Seat height adjustment | Seat height adjustment infinitely variable: Self-supporting safety gas spring low: 400 - 445 mm; Self-supporting safety gas spring high: 475 - 610 mm. | Even for people taller than 192 cm and smaller than 151 cm is offered the correct ergonomic seating posture. |
|------------------------|--|---|
| Castors/Glides | Soft double castors, black, load dependent braked, for hard floors or glides. (Acc. to DIN EN 12529). | The chair does not roll away in an off-loaded position. |
| Base | Brilliant silver or polished aluminium base. | Very high stability, long service life. High-quality look. |
| Seat depth adjustment | Sliding seat for an individual adjustment of the seat depth, area of adjustment: 60 mm. | The seat depth can be individually adjusted to ensure an optimal support surface of the thighs. Too little (lack of support) or too much (congestion of the bloodstream in the region of the popliteal fossa) can be avoided. |
| Lumbar support | Height adjustable (50 mm) or height (70 mm) and depth adjustable (up to 15 mm). | The lumbar support is height adjustable or height and depth adjustable and can be adapted to the corporal conditions of the user. |
| Armrests | 2D T-armrests, height and width adjustable, soft surface. 3D T-armrests, height, width and depth adjustable, soft surface. 4D T-armrests, height, width and depth adjustable, rotatable, soft surface. | The armrests relieve the neck and shoulder muscles. |
| Material (fabric) | Various fabric and leather options are available as well as different mesh colours. | Individual design. |
| Accessories | Coat hanger, black or white. | |