

Technical data sheet HU150

Specification HUB screen low, partition wall,low

Dimensions in mm

Total:

H: 1350

W (no ArmR): 1000

D: 425

Packaging data

Basic equipment

Weight: Volume: kg

m³



Benefit

General Perfect sound absorption and insulation. Sound-absorbing polyester panels integrated across entire surface, 50 mm thick. Frame Attractive look. Aluminium profile frame. 1000 x 1350 x 55 mm (W x H x D), in black or white. Cover Covered with laminated fabric on both sides. Can be used as a notice board. Cover materials Various fabric qualities in various colours. Individual design. Metal parts Steel base, powder-coated in black or white. Optimum stability. Inlaid material All materials are unmixed and recyclable. Environmentally friendly. Standards High level of safety. GS-symbol for tested safety. Tested for absence of harmful substances. Certification High-quality product. Quality management system DIN EN ISO 9001:2015, Regulation (EC) no. 1221/2009 (EMAS), Environmental Management System DIN EN ISO 14001:2015, Occupational Health and Safety Management System ISO 45001:2018, EcoVadis Gold. Warranty and returns Quality guaranteed to last for entire product life. 10 year warranty according to our current

Disassembly instructions are available upon request for any interstuhl product

warranty conditions.



Technical data sheet HU150

Specification HUB screen low, partition wall,low

Dimensions in mm

Total:

H: 1350

W (no ArmR): 1000

D: 425

Packaging data

Weight: Volume:

kg : m³



Options		Benefit
Connecting element	Connecting element to link several individual screens, in black or white.	Flexible extension.
Practical hook	Practical steel hook in black or white.	For hanging up jackets, flip charts or whiteboards.
Whiteboard	Whiteboard incl. 2 practical hooks in black or white.	Additional function.

Disassembly instructions are available upon request for any interstuhl product