

Technical data sheet HUW65

Specification HUB board, mobile board high with dec. stitching

Dimensions in mm

Total:	H:	1900
	W (no ArmR):	1100
	D:	520

Packaging data	Weight:	kg
	Volume:	m³



Basic equipment

Benefit

Frame	Aluminium profile frame. 1100 x 1900 x 55 mm (W x H x D), in black or white.	Attractive look.
Cover	Covered with laminated fabric on both sides, decorative seams on one side. Brown leather strap.	Visual highlight.
Cover materials	Various fabric qualities in various colours.	Individual design.
Metal parts	Legs made from sturdy high-pressure die cast aluminium, powder-coated in black or white.	Optimum stability.
Castors	Lockable double castors in black or white.	Mobile while retaining firm contact with the floor.
Inlay	Cover inlaid in aluminium leg. Plastic inlay in same colour as frame (black or white).	
Materials used	All materials are unmixed and recyclable.	Environmentally friendly.
Standards	GS-symbol for tested safety. Tested for absence of harmful substances.	High level of safety.
Certification	Quality management system DIN EN ISO 9001:2015, Regulation (EC) no. 1221/2009 (EMAS), Environmental Management System DIN EN ISO 14001:2015, Occupational Health and Safety Management System ISO 45001:2018, EcoVadis Gold.	High-quality product.
Warranty and returns	10 year warranty according to our current warranty conditions.	Quality guaranteed to last for entire product life.

Disassembly instructions are available upon request for any interstuhl product

Technical data sheet HUW65

Specification HUB board, mobile board high with dec. stitching

Dimensions in mm

Total:	H:	1900
	W (no ArmR):	1100
	D:	520

Packaging data	Weight:	kg
	Volume:	m ³



Options

Benefit

Covered inlay	With fabric same as screen cover.	Visual highlight.
Practical hook	Practical steel hook in black or white.	For hanging up jackets, flip charts or whiteboards.
Whiteboard	Whiteboard incl. 2 practical hooks in black or white.	Additional function.

Disassembly instructions are available upon request for any interstuhl product