Technical data sheet SU134

Specification Visitor chair, Sled-base, fully upholstered

Dimensions in mm	Backrest:	H:	400
	Seat:	H:	440
		W:	460
		D:	450
	Total:	H:	825
		W (no ArmR):	515
		W (ArmR):	580
		D:	525
Packaging data	Weight:	kg	9,9
	Volume:	m³	0,3



Basic equipment		Benefit
Seat and Backrest	Seat and back: polypropylene shell with Flex-Function. Ergonomically shaped; fully upholstered.	High quality appearance and ergonomic sitting.
Upholstery	Foam thickness: 10 mm, pad thickness approx. 15 mm.	Good seating comfort.
Frame	Sled-base: Steel tube, powder-coated, white or black. Round tube Ø: 12 mm.	Very good stability, longevity. The coating ensures an attractive surface even with intensive use.
Stackability	Stacking height: 5 pieces. Stacking protection included. Only stackable without armrests.	Space-saving stowage possibility.
Glides	Plastic glides for soft floors, black.	Optimum stability.
Materials	All materials are pure and recyclable.	Environmentally friendly.
Standards	GS-symbol for tested safety, tested for contaminants. BIFMA tested.	High level of safety and comfort.
Certification	Quality Management System DIN EN ISO 9001:2015, Regulation (EC) no. 1221/2009 (EMAS), Environmental Management System DIN EN ISO 14001:2015, Occupational Health and Safety Management System DIN EN ISO 45001:2018, Energy Management System DIN EN ISO 50001:2018, EcoVadis Gold. Commitment to sustainability. Blue Angel, Bifma e3 level Platin.	High-quality product.
Warranty	10 year warranty according to our current warranty conditions.	Quality guaranteed to last for entire product life.

Technical data sheet SU134

Specification Visitor chair, Sled-base, fully upholstered

Dimensions in mm	Backrest:	H:	400		
	Seat:	H:	440		
		W:	460		
		D:	450		
	Total:	H:	825		
		W (no ArmR):	515		
		W (ArmR):	580		
		D:	525		
Packaging data	Weight:	kg	9,9		
	Volume:	m³	0,3		
Options				Benefit	
P • • • • •				benem	
laterials (fabric)		Various fabrics i available.	n a variety of colours are	Individual design.	
rame	Sled-base: Steel tube, chromed. Round tube Ø: 12 mm.		Very good stability, longevity. High quality appearance.		
Glides		Felt glides for hard floors, black.		Optimum stability of the chair. Spares the floor.	
Armrests			loop armrest (round tube Ø16 lour with black rubber pad.	The armrests relieve the neck and shoulder muscles.	
ow connector Extendable row connector, chrome-plated.					

interstuhl