

Technical data sheet SU174

Specification Visitor chair, pyramid base, fully upholstered

Dimensions in mm	Backrest:	H:	400
	Seat:	H:	440
		W:	460
		D:	450
	Total:		
		H:	825
		W (no ArmR):	460
		W (ArmR):	580
		D:	515
Packaging data	Weight:	kg	8,1
	Volume:	m³	0,3



Basic equipment		Benefit
Seat and Backrest	Seat and back: polypropylene shell with Flex-Function. Ergonomically shaped; fully upholstered.	High quality appearance and ergonomic sitting.
Upholstery	Foam thickness: 10 mm, pad thickness approx. 15 mm.	Good seating comfort.
Frame	Pyramid base: Steel tube, powder-coated, white or black. Round tube Ø: 18 mm. Wall thickness: 2 mm.	Very good stability, longevity. The coating ensures an attractive surface even with intensive use.
Glides	Plastic glides for soft floors, black.	Optimum stability.
Materials	All materials are pure and recyclable.	Environmentally friendly.
Standards	GS-symbol for tested safety, tested for contaminants. BIFMA tested.	High level of safety and comfort.
Certification	Quality Management System DIN EN ISO 9001:2015, Regulation (EC) no. 1221/2009 (EMAS), Environmental Management System DIN EN ISO 14001:2015, Occupational Health and Safety Management System DIN EN ISO 45001:2018, Energy Management System DIN EN ISO 50001:2018, EcoVadis Gold. Commitment to sustainability. Blue Angel, Bifma e3 level Platin.	High-quality product.
Warranty	10 year warranty according to our current warranty conditions.	Quality guaranteed to last for entire product life.



Technical data sheet SU174

Specification Visitor chair, pyramid base, fully upholstered

Dimensions in mm	Backrest:	H:	400
	Seat:	H:	440
		W:	460
		D:	450
	Total:	116	205
		H:	825
		W (no ArmR):	460
		W (ArmR):	580
		D:	515
Packaging data	Weight:	kg	8,1
	Volume:	m³	0,3



	Benefit	
Various fabrics in a variety of colours are available.	Individual design.	
Pyramid base: Steel tube, chromed. Round tube Ø: 18 mm. Wall thickness: 2 mm.	Very high stability, longevity. High quality appearance.	
Felt glides for hard floors, black.	Optimum stability of the chair. Spares the floor.	
Open armrest or loop armrest (round tube Ø16 mm) in frame colour with black rubber pad.	The armrests relieve the neck and shoulder muscles.	
	Pyramid base: Steel tube, chromed. Round tube Ø: 18 mm. Wall thickness: 2 mm. Felt glides for hard floors, black. Open armrest or loop armrest (round tube Ø16	